

00299-9WH : with 9X3W White high power LED.
 00299-9BU : with 9X3W Blue high power LED.
 00299-9GN : with 9X3W Green high power LED.

SPECIFICATION

Housing description: Made of SS316

Operating voltage: DC 10–30 Volts

!Notice!

”The underwater light warranty only covers the replacement of defective parts, not the towing, launching and replacement costs.”

INSTALLATION INSTRUCTION

1. This light is designed with water cooling system, **DO NOT** obstruct the water cooling passages behind the light. **MUST BE** installed under waterline and used only when **SUBMERGED**.
2. For 3 mounting holes, drill 9/64” diam. x 1/2” deep & countersink 1/4”, fill up the countersinks with sealant
3. For wire passage hole, drill 16mm diam. x 14mm deep, in the center of this hole drill 1/4” hole through the transom.
4. In the back of the light, overfill the cup around the wire with sealant and slide the wire through the transom. Do not put sealant outside of the cup.
5. Place the light over the holes and push slowly to allow the sealant to fill the center hole in the transom, then tight the 3 screws.
6. Secondary optics placed over the surface of the TIR lens to increase brightness.

WIRING DIAGRAM for

00299-9WH/00299-9BU/00299-9GN

!Notice!

Connect the light at first before connect to Power
This is for Safety

